

POCm-DOCKING-6BAY

POCm Charging Docking Station



Features

- » 6-bay stackable charging station
- » Built-in 300W power

Specifications

| I/O Interface | |
|------------------------------|--|
| I/O Interface | 1 x AC-in: C13 connector |
| Indicator&Buttons | |
| Buttons | 1 x Power on/off |
| Indicators | 1 x Power LED (Orange) |
| | 6 x Battery LED (Blue/ Orange) |
| | Charging Battery: Orange |
| | Fully Charged Battery: Green |
| Physical Characteristics | |
| Color | White |
| Thermal | Smart Fan |
| Chassis Construction | Metal housing |
| Construction Material | SECC |
| Mounting | VESA 100 compliant |
| Weight (Net) (kg) | 0.8 kg |
| Weight (Gross) (kg) | 4.49 kg |
| Dimensions (LxWxH) (mm) | 273.8 x 122 x 301.8 |
| Battery | |
| Battery Pack Type | 3 x 3S3P cells Lithium-ion Battery |
| Battery Pack Capacity | 3 x 9000 mAh (3 x 97Wh) |
| | 3 x 7800 mAh (3 x 87Wh) |
| Normal Voltage | 10.8V |
| Battery Life Time | 300 cycles > 70% |
| Charge Voltage | 12.6V |
| Continuous Charge Current | 2A for each battery |
| Continuous Discharge Current | 5A (each battery pack Discharge Power < 55.5W at 40°C) |
| Maximum Discharge Current | 7A (each battery pack Discharge Power < 77.7W at 25°C) |
| Discharge Cut-off Voltage | 9V |
| Power | |
| Input | 100 – 240VAC |
| Power Adapter | 300W power adapter |
| Environment | |
| Operating Temperature | 0°C ~ 40°C |
| Storage Temperature | -20°C ~ 60°C |

| | |
|---------------------|--|
| Humidity | 10% ~ 90% (non-condensing) |
| Vibration | 1G |
| Operating Shock | 5G peak acceleration (11ms duration) |
| Non-operating shock | 15G peak acceleration (11ms duration) |
| Certifications | |
| Safety & EMC | FCC Part18 |
| | EN 62368-1 Ed.2 |
| | EN 55032 + EN 55035 (60601-1-2 Compatible) |
| | Battery Pack: UN38.3, IEC62133, IEC62368-1 |

Ordering Information

| | |
|-----------------------|--|
| POCm-DOCKING-6BAY-R11 | 6 Bay Smart Charging Docking, with internal 300 watts PSU, Stackable, Fast Charging, R11 |
|-----------------------|--|