

Robot-TP-84M

8.4" Teaching Pendant



Features

- » 350 nits high luminance control terminal with touchscreen to present its graphical user interface.
- » 6-meter long all-in-one cable allows easy installation
- » Ergonomic body design, easy to operate

Specifications

| | |
|--------------------------|------------------------------------|
| Dimensions | |
| Dimensions | 321.67 x 204 x 81.41 |
| Environment | |
| Humidity | < 90% RH (no condensation allowed) |
| Operating Temperature | 0°C~50°C |
| Storage Temperature | - 20°C ~ 65°C |
| LCD | |
| Backlight MTBF | 50000 |
| Brightness (cd/m2) | 350 |
| Contrast Ratio | 600:1 |
| LCD Color | 262K |
| Pixel Pitch (mm) | 0.207 x 0.207 |
| Resolution | 800(W) x 600 (H) |
| Size | 8.4" |
| Viewing Angle (H-V) | 130° / 150° |
| Physical Characteristics | |
| Color | Black |
| Touch | |
| Touch Screen | Resistive Touch Screen |

Ordering Information

| | |
|-----------------------|--|
| Robot-TP-84M/K-R11 | |
| Robot-TP-84M-R11 | |
| Robot-TP-84M/K-ML-R11 | 8.4" 350cd/m ² SVGA TFT LCD teach pendant with touch screen, key switch, 3-position dead-man switch, emergency button, 37-pin military connector, R11 |