

# ACE-A160A

600 W PS/2 ATX Power Supply with ErP



## Features

600 W PS/2 ATX Power Supply with ErP

## Specifications

| General                  |   |
|--------------------------|---|
| Dimensions               | 140 x 150 x 86  |
| Efficiency               | 85%   |
| MTBF                     | 100,000   |
| Operating temperature    | -5°C ~ 50°C   |
| Output Connector         | 1 x 20+4-pin ATX, 1 x 4-pin 12V CPU, 9 x HDD/CDROM, 2 x FDD, 2 x SATA, 1 x Extra +5V(P10) |
| Storage temperature      | -40°C ~ 80°C  |
| Watt                     | 600W  |
| Input                    |   |
| Voltage                  | 90~265 VAC Full Range   |
| Frequency                | 47 Hz ~ 63 Hz   |
| Input Current            | 10A (RMS)@115VAC, 5A (RMS)@230VAC   |
| Inrush Current           | 40A max. for 115VAC<br>80A max. for 230VAC  |
| Output                   |   |
| Voltage                  | +3.3V/25A,+5V/25A,+12V1/16A,+12V2/16A,+12V3/16A,+12V4/16A,-12V/0.5A,+5Vsb/4A              |
| Over Voltage Protection  | 5V: 5.7V-6.5V<br>12V1 ~ 12V4: 13.3V-16.7V<br>3.3V: 3.9V-4.5V                              |
| Short Circuit Protection | +3.3V, +5V, +12V1, +12V2, +12V3, +12V4, 24V<br>or -12V shutdown and latch off             |

## Ordering Information

|               |  |
|---------------|--|
| ACE-A160A-R11 | 600W PS/2 ATX Power Supply with ERP;CCL;RoHS |
|---------------|--|