

AFL-07A-LX

AMD Geode™ LX 800 500 MHz Processor



Features

- » 7" widescreen WVGA LED backlight TFT LCD with resistive touch screen
- » 9V~28V wide range DC power input (for Intel® N2600 platform)
- » Compact design with plastic housing
- » Fanless cooling system
- » Selectable AT/ATX power mode
- » System memory up to 2 GB SDRAM
- » Built-in 802.11b/g/n Wireless LAN
- » Built-in speakers
- » One compactFlash® slot
- » IP 64 compliant front panel
- » IEI One Key Recovery solution allows you to create rapid OS backup and recovery (suggest with over 4GB storage capacity)

Specifications

Communication	
Wi-Fi	IEEE 802.11 b/g
Dimensions	
Dimensions	226 x 140 x 41
Environment	
Operating Temperature	-10°C~50°C
Storage Temperature	-20°C~60°C
I/O Interface	
I/O Ports and Switches	1 x RS-232 COM Port
	1 x RS-232/422/485 COM Port
	2 x RJ-45 for 10/100Mbps LAN
	2 x USB 2.0
	1 x Power Switch
	1 x Reset Button
	1 x Power Jack
	1 x Audio Jack (Line-out)
RAM	Supports one 333MHz or 400MHz DDR SO-DIMM (1GB Max.)
LCD	
Backlight MTBF	50000 (LED backlight panel)
Brightness (cd/m2)	500
Contrast Ratio	400:1
LCD Color	262K
Pixel Pitch (mm)	0.0635 (H) x 0.1905 (V)
Resolution	800 x 480
Size	Wide 7"
Viewing Angle (H-V)	140° / 110°
Other Features	
System Cooling	Fanless

Power	
Power Requirement	12 VDC
Storage	
Storage	CF Type II
System	
Chipset	AMD LX800 + AMD CS5536
CPU	AMD Geode™ LX 800 (500Mhz)
Weight	
Weight	0.6Kg
I/O Interface	
I/O Interface	2 x USB 2.0
	1 x Reset Button
	1 x RS-422/485
	1 x RS-232
	1 x Power Switch
	LAN(RJ-45 for 10/100Mbps LAN)
	1 x Audio((line-out))
	1 x DC Input Jack

Ordering Information

AFL-07A-LX/R/512-R23	7" 500 cd/m ² , WVGA fanless panel PC with AMD LX-800 CPU, AT/ATX mode, 802.11b/g Wireless Module, Touch screen and 512MB DDR RAM, R23
----------------------	---

Packing List

4 x Screw Pack M3-5mm	1 x Power Adpater
1 x Touch Pen	1 x RJ45 to RS-232 Transfer Cable