

DM-F08A

6.5"~15" DM-F IP65 Industrial Monitor



Features

- » Robust IP65 aluminum front bezel
- » Aesthetic ultra-thin bezel for seamless panel mount installation
- » DC input
- » DVI / VGA flexible video input solution
- » Resistive single touch
- » Wide temperature support

Specifications

| Display | |
|--------------------------|---|
| LCD Size | 8"(4:3) |
| Brightness(cd/m2) | 500 |
| Max Resolution | 800 (W) x 600 (H) |
| Contrast Ratio | 500:1 |
| Backlight MTBF(hrs) | 50000 |
| I/O Interface | |
| I/O Ports and Switches | 1 x VGA (DB-15) |
| | 1 x DVI |
| | 1 x USB 2.0 (touch) |
| | 1 x RS-232 (reserved for resistive touch ATO) |
| | 1 x Lockable 12V DC jack |
| Power | |
| Power adapter | 12V DC |
| Environment | |
| Operating Temperature | -20°C ~ 60°C (with air flow) |
| Humidity | 10% to 95% (non-condensing) |
| Storage Temperature | -20°C ~ 70°C |
| IP Level | IP 65 compliant front panel |
| Physical Characteristics | |
| Dimensions (LxWxH) (mm) | 222.2 x 182.2 x 42.7 |
| Cutout Dimensions | 206 x 154 |
| Weight | |
| Weight | 1.33/4.5 |
| LCD | |
| LCD Color | 262K |
| Pixel Pitch (mm) | 0.0675 x 0.2025 |
| Viewing Angle (H-V) | 140°/120° |
| Touch | |
| Touch Screen | 5-wire resistive single touch window |

Touch Controller

Penmount 6000

Ordering Information

DM-F08A/R-R21

8" 500 cd/m² SVGA LCD monitor, Aluminum front panel, Black color, W/ USB resistive touch screen, 12V DC input, Powder paint, R21

Packing List

1 x Touch Pen

1 x USB Cable

1 x VGA Cable

1 x Adapter

1 x AC power cord