

BRICK-NANO

Embedded Chassis for IEI DC input EPIC/3.5" SBC

Features

- » Designed for EPIC / 3.5" SBC with DC input
- » Flexible SBC compatibility
- » One 2.5" hard drive capacity
- » Cost-effective, RoHS compliant design



BRICK Chassis with WAFER-AL (SBC not included)

Specifications

Form factor	
SBC Form Factor	Refer to NANO/WAFER Series
I/O Interface	
I/O Openings	Reserved IO window for COM port expansion
I/O Ports	Refer to SBCs
Expansion Slots	
Expansion Slots	Refer to SBCs
System	
Cooling method / System Fan	Refer to SBCs
Drive Bays	1 x 2.5" HDD bay
Indicator&Buttons	
Buttons	Power switch with LED
Color	
Color	Black
Dimensions	
Dimensions	220 x 143 x 55 mm
Weight	
Weight	1.2kg/1.5kg
Environment	
Operating Temperature	0°C ~ 40°C

Ordering Information

BRICK-WAFER-BT-R10	Embedded chassis for WAFER-BT SBC, with SATA cable, IO bracket ,power switch, DC input cable, mat black and RoHS
BRICK-WAFER-AL-R10	Embedded chassis for WAFER-AL SBC, with SATA cable, IO bracket ,power switch, DC input cable, mat black and RoHS
BRICK-NANO-BT-R10	Embedded chassis for NANO-BT SBC, with SATA cable, IO bracket ,power switch, DC input cable, mat black and RoHS

BRICK-NANO-AL-R10

Embedded chassis for NANO-AL SBC, with SATA cable, IO bracket ,power switch, DC input cable, mat black and RoHS

Packing List

1 x BRICK Chassis	1 x Power switch cable
1 x Screw set	1 x QIG
1 x SATA cable	