

# ACE-A622C

1U flex ATX 220W Power Supply



## Features

1U flex ATX 220W Power Supply

## Specifications

General	
Dimensions	150 x 81.5 x 40.5
Efficiency	85%
MTBF	100000
Operating temperature	0°C ~ 50°C
Output Connector	1 x 20+4-PIN ATX, 1 x 4-pin 12V CPU, 2 x HDD/CDROM, 1 x Graphics card power, 2 x SATA
Storage temperature	-20°C ~ 80°C
Watt	220
Input	
Voltage	90~264 VAC Full Range
Frequency	47 Hz ~ 63 Hz
Input Current	4A (RMS)@115VAC, 2A (RMS)@230VAC
Inrush Current	80A max. for 115VAC, 160A max. for 230VAC
Output	
Voltage	+3.3V/10A,+5V/14A,+12V/14A,-12V/0.3A,+5Vsb/2.5A
Over Voltage Protection	+3.3V: 3.7V-4.8V +5V: 5.55V-7.0V +12V1 : 13.3V-16V
Short Circuit Protection	+3.3V, +5V, +12V, -12V shutdown and latch off

## Ordering Information

ACE-A622C-R10	1U flex ATX 220W Power Supply;90~264VAC;ERP;CCL;RoHS
---------------	------------------------------------------------------