

PUZZLE-7030A

1U Rackmount Network Appliance with Intel® Xeon® D Processor series (Code Name: Ice Lake-D LCC)



Features

- » Intel® Xeon® D Processor series (Code Name: Ice Lake-D LCC)
- » 4 x DDR4 2400M/2933Hz ECC UDIMM/RDIMM, up to 256G
- » 8 x 2.5 Gbps RJ-45 LAN ports & 5 x 10 Gbps SFP+ ports
- » 1 x FH PCIe Gen4 x8 or 2 x FH PCIe Gen4 x4 and 1 x OCP 3.0 slot
- » 1 x RJ-45 Console, 2 x USB 3.0, LCM
- » 2 x 2.5" SATA slot, 2 x M.2 M key 2280 (SATA/PCIe Gen3 x2), 1 x M.2 B key for IPMI module (support IEI iRIS2 IPMI module)
- » 320W Redundant Power Supply

Specifications

| | |
|-----------------------------|--|
| Form Factor | |
| Form Factor | 1U |
| System | |
| CPU | Intel® Xeon® D Processor series (Code Name: Ice Lake-D LCC) |
| Chipset | Integrated in CPU |
| Memory | DDR4 2400M/2933Hz ECC UDIMM/RDIMM |
| Memory Max. | Up to 256G |
| Cooling method / System Fan | 3x Cooling Fans with Smart Fan 1 x System Fan |
| Physical Characteristics | |
| Rack Height | 1U |
| Dimensions (LxWxH) (mm) | 436.2 x 454.3 x 44.2 |
| Storage | |
| Storage | 2 x 2.5" SSD/HDD Bay : support SATA 3.0 (6 Gbps) |
| I/O Interface | |
| Ethernet | 5 x SFP+ : 10 GbE 8 x LAN : 2.5 GbE RJ45 (Intel®KTI225V) |
| I/O Interface | 1 x Console port(s) : RJ45 2 x USB 3.0 |
| Expansion | PCIe x8 : 1 x FH PCIe Gen4 x 8 or 2 x FH PCIe Gen4 x 4 3 x M.2(NGFF) : 2 x M key 2280 (SATA/PCIe Gen3 x2) 1 x B key for IPMI module (support IEI iRIS2 IPMI module) |
| Power | |
| Power Supply | 320W Redundant Power Supply |
| Environment | |
| Operating Temperature | 0°C ~ 40°C (32°F ~ 104°F) |
| Storage Temperature | -10°C ~ 50°C |
| Humidity | 5% ~ 90% non-condensing |
| Certifications | |
| Safety & EMC | By customer request |
| OS Support | |
| OS Support | Ubuntu, Linux based OS |

Ordering Information

| | |
|------------------|--|
| PUZZLE-7030A-R20 | 1U Rackmount Network Appliance with Intel Ice Lake-D LCC processor |
|------------------|--|

Packing List

| | |
|-------------------------------|------------------------|
| 2 x Power cord | 2 x Rack mounting ears |
| 6 x Screw for 2.5-inch drives | |