

# TANK-720-Q67

Intel® 2nd Gen Core™ Desktop Processor



## Features

- » 2nd Gen Intel® Core™ i7/i5/i3 or Celeron® mobile processors for TANK-700 2nd Gen Intel® Core™ i7/i5/i3 Pentium® and Celeron® desktop processors for TANK-720
- » Intel® HD graphics supports H.264/AVC-MPEG2/VC1, DirectX 10.1 and OpenGL 3.0
- » On-board 2GB DDR3 memory and one DDR3 SO-DIMM slot (system max. 10 GB)
- » Dual combo (10/100/1000 BASE-T(X) or 1000 baseSFP slot RJ-45 port) Gigabit LAN ports, supporting Intel® AMT 7.0
- » Supports 8-channel audio/video capture and dual display by VGA and HDMI™
- » Dual-band 2.4/5 GHz 802.11 a/b/g/n 3T3R MIMO Wi-Fi for high speed wireless transmission

## Specifications

## Ordering Information

TANK-720-Q67-i5/2G-R21	Fanless embedded system , Core i5 Dual Core 2xxT CPU (Above 2.7GHz), TDP 35W, 2GB DDR3 on board memory , VGA/HDMI™, USB3.0, 2 x SATA3.0, SFP Fiber, Isolated CAN, Audio, 9-36V DC input, -20~50°C, R21, RoHS
TANK-720-Q67-i3/2G-R21	Fanless embedded system , Core i3 Dual Core 2xxT CPU (Above 2.5GHz), TDP 35W, 2GB DDR3 on board memory , VGA/HDMI™, USB3.0, 2 x SATA3.0, SFP Fiber, Isolated CAN, Audio, 9-36V DC input, -20~50°C, R21, RoHS
TANK-720-Q67-P/2G-R21	Fanless embedded system , Pentium Dual Core G6xxT CPU (Above 2.2GHz), TDP 35W, 2GB DDR3 on board memory , VGA/HDMI™, USB3.0, 2 x SATA3.0, SFP Fiber, Isolated CAN, Audio, 9-36V DC input, -20~50°C, R21, RoHS

## Packing List

1 x Pluggable DC-in Terminal Block	1 x Pluggable CAN-bus Terminal Block
1 x Pluggable Remote Control Terminal Block	4 x RJ-45 to DB-9 COM Port Cable
1 x Power Cord Convert Cable	1 x Power Cord
1 x Power Adapter	2 x Mounting Bracket
8 x Mounting Bracket Screws	