

# DM-F65A

6.5"~15" DM-F IP65 Industrial Monitor



## Features

- » Robust IP65 aluminum front bezel
- » Aesthetic ultra-thin bezel for seamless panel mount installation
- » DC input
- » DVI / VGA flexible video input solution
- » Resistive single touch
- » Wide temperature support

## Specifications

Display	
Backlight MTBF(hrs)	50000
Brightness(cd/m2)	800
Contrast Ratio	600:1
LCD Size	6.5"(4:3)
Max Resolution	640 (W) x 480 (H)
Environment	
Humidity	10% to 95% (non-condensing)
IP Level	IP 65 compliant front panel
Operating Temperature	-20°C ~ 60°C (with air flow)
Storage Temperature	-20°C ~ 70°C
I/O Interface	
I/O Ports and Switches	1 x VGA (DB-15)
	1 x DVI
	1 x USB 2.0 (touch)
	1 x RS-232 (reserved for resistive touch ATO)
	1 x Lockable 12V DC jack
LCD	
LCD Color	16.2M
Pixel Pitch (mm)	0.207 x 0.207
Viewing Angle (H-V)	160° / 140°
Physical Characteristics	
Cutout Dimensions	180 x 140
Dimensions (LxWxH) (mm)	191.8 x 154.36 x 42.88
Power	
Power adapter	12V DC
Touch	
Touch Controller	Penmount 6000
Touch Screen	5-wire resistive single touch window

Weight	
Weight	1.1/2.6 Kg

## Ordering Information

DM-F65A/R-R10	6.5" 800 cd/m <sup>2</sup> High luminance VGA LCD monitor with VGA, Aluminum die casting front panel, Black color,W/ USB resistive touch screen, R10
---------------	--

## Packing List

1 x Touch Pen	1 x USB Cable
1 x VGA Cable	1 x Adapter
1 x AC power cord	