

EBC-3300

Embedded Chassis for IEI thin Mini-ITX SBC



Features

- » Designs for thin type Mini-ITX SBC with single voltage input
- » Total height 42mm for space critical application
- » One 2.5" hard drive capacity
- » Flexible E-Window tool kit support

Specifications

| | |
|--------------------------|---------------------------------|
| Form factor | |
| SBC Form Factor | Refer to SBC |
| I/O Interface | |
| I/O Ports | 2 x USB3.0 |
| | 2 x LAN |
| | Refer to SBC |
| Expansion Slots | |
| Expansion Slots | 2 slot |
| System | |
| Drive Bays | 1 x 3.5" (front accessible/HDD) |
| Indicator&Buttons | |
| Buttons | Power switch |
| Indicators | Power, HDD |
| Physical Characteristics | |
| Construction | Heavy duty metal |
| Color | |
| Color | Black |
| Dimensions | |
| Dimensions | 190 x 190 x 43 |
| Weight | |
| Weight | 1 kg/ 2kg |
| Environment | |
| Operating Temperature | -10°C ~ 50°C |
| Humidity | 10% ~ 95%, non-condensing |

Ordering Information

| | |
|-------------------|---|
| EBC-3300-ULT3-R10 | Embedded chassis for tKINO-ULT3 with one 2.5" SATA hard drive bay, IO bracket, one LED cable, one power switch cable and RoHS |
| EBC-3300-BW-R10 | Embedded chassis for tKINO-BW with one 2.5" SATA hard drive bay, IO bracket, one LED cable, one power switch cable and RoHS |
| EBC-3300-AL-R10 | Embedded chassis for tKINO-AL with one 2.5" SATA hard drive bay, IO bracket, one LED cable, one power switch cable and RoHS |

| | |
|---------------------|----------------------------|
| Packing List | 1 x Wall mount bracket kit |
| 1 x Screw set | |