

BRICK-KINO

Embedded Chassis for IEI DC input Mini-ITX SBC

Features

- » Designed for Mini-ITX SBCs with DC input
- » Flexible SBC compatibility
- » One 2.5" hard drive capacity
- » Cost-effective, RoHS compliant design



BRICK Chassis with eKINO-BT (SBC not included)

Specifications

| | |
|-----------------------------|---|
| Form factor | |
| SBC Form Factor | Refer to KINO Series |
| I/O Interface | |
| I/O Openings | Reserved IO window for COM port expansion |
| I/O Ports | Refer to SBCs |
| Expansion Slots | |
| Expansion Slots | Refer to SBCs |
| System | |
| Cooling method / System Fan | Refer to SBCs |
| Drive Bays | 1 x 2.5" HDD bay |
| Indicator&Buttons | |
| Buttons | Power switch with LED |
| Color | |
| Color | Black |
| Dimensions | |
| Dimensions | 203 x 178 x 64 mm |
| Weight | |
| Weight | 1.25kg/1.5kg |
| Environment | |
| Operating Temperature | 0°C ~ 40°C |

Ordering Information

| | |
|----------------------|--|
| BRICK-tKINO-ULT3-R10 | Embedded chassis for tKINO-ULT3 SBC, with IO bracket ,power switch, mat black and RoHS |
| BRICK-tKINO-BW-R10 | Embedded chassis for tKINO-BW SBC, with IO bracket ,power switch, mat black and RoHS |
| BRICK-tKINO-AL-R10 | Embedded chassis for tKINO-AL SBC, with IO bracket ,power switch, mat black and RoHS |
| BRICK-eKINO-BT-R10 | Embedded chassis for eKINO-BT SBC, with IO bracket ,power switch, mat black and RoHS |
| BRICK-KINO-DBT-R10 | Embedded chassis for KINO-DBT SBC, with IO bracket ,power switch, mat black and RoHS |

BRICK-KINO-DAL-R10

Embedded chassis for KINO-DAL SBC, with IO bracket ,power switch, mat black and RoHS

Packing List

| | |
|-------------------|------------------------|
| 1 x BRICK Chassis | 1 x Power switch cable |
| 1 x Screw set | 1 x QIG |