

# BRICK-KINO

Embedded Chassis for IEI DC input Mini-ITX SBC

## Features

- » Designed for Mini-ITX SBCs with DC input
- » Flexible SBC compatibility
- » One 2.5" hard drive capacity
- » Cost-effective, RoHS compliant design



BRICK Chassis with eKINO-BT (SBC not included)

## Specifications

Form factor	
SBC Form Factor	Refer to KINO Series
I/O Interface	
I/O Openings	Reserved IO window for COM port expansion
I/O Ports	Refer to SBCs
Expansion Slots	
Expansion Slots	Refer to SBCs
System	
Cooling method / System Fan	Refer to SBCs
Drive Bays	1 x 2.5" HDD bay
Indicator&Buttons	
Buttons	Power switch with LED
Color	
Color	Black
Dimensions	
Dimensions	203 x 178 x 64 mm
Weight	
Weight	1.25kg/1.5kg
Environment	
Operating Temperature	0°C ~ 40°C

## Ordering Information

BRICK-tKINO-ULT3-R10	Embedded chassis for tKINO-ULT3 SBC, with IO bracket ,power switch, mat black and RoHS
BRICK-tKINO-BW-R10	Embedded chassis for tKINO-BW SBC, with IO bracket ,power switch, mat black and RoHS
BRICK-tKINO-AL-R10	Embedded chassis for tKINO-AL SBC, with IO bracket ,power switch, mat black and RoHS
BRICK-eKINO-BT-R10	Embedded chassis for eKINO-BT SBC, with IO bracket ,power switch, mat black and RoHS
BRICK-KINO-DBT-R10	Embedded chassis for KINO-DBT SBC, with IO bracket ,power switch, mat black and RoHS

BRICK-KINO-DAL-R10

Embedded chassis for KINO-DAL SBC, with IO bracket ,power switch, mat black and RoHS

## Packing List

1 x BRICK Chassis	1 x Power switch cable
1 x Screw set	1 x QIG