


iRIS-1010

IPMI 2.0 adapter card with AST1010 BMC chip (W/O KVM over IP function) for mini PCIe socket interface



Features

1. IPMI 2.0 based remote management
2. Out-of-Band management
3. Hardware health monitor
4. Remote power control

Specifications

Physical Characteristics	
Dimensions (LxWxH) (mm)	30mm x 30mm
Net Weight	4g
Storage	
Storage	Description:IPMI 2.0 adapter card with AST2400 BMC chip for DDR3 SO-DIMM
Other Features	
iRIS	--- IPMI 2.0 Based Management --- » BMC stack with a full IPMI 2.0 implementation » Customizable sensor management --- OS Platform Independent --- --- Hardware Health Monitor --- » System/CPU temperature » Fan speeds » Voltage » Chassis intrusion » Power supply failed » FRU (Field Replaceable Unit) --- Event Log --- » BIOS event » Hardware health monitor event » Sensor readings --- Notifications --- » Email alerts » SNMP traps --- LDAP Support --- » Direct LDAP support from the device » Open LDAP (Generic LDAP) supported --- Media Redirection --- » Simultaneous floppy, Hard disk or USB and CD or DVD redirection

	» Efficient USB 2.0 based CD/DVD redirection with a typical speed of 20XCD
	» Support for USB key
	» Completely secured (Authenticated or Encrypted) remote KVM or virtual media
	--- Remote Power Control ---
	» Remote power control
	» Serial over LAN (SOL)
	--- User Management ---
	» IPMI based user management
	» Added security with SSL (HTTPS)
	» Multiple user permission level
	» Multiple user profiles
	--- Web-based Configuration ---
	» Full configuration using web UI
	» Fail-safe firmware upgrade
	» Multi-language support in Web interface with English as the currently supported language

Ordering Information

iRIS-1010-R10	IPMI 2.0 adapter card with AST1010 BMC chip (W/O KVM over IP function) for mini PCIe socket interface
---------------	---