

Power Supply > 1U/2U Power Supply

# 63030-010150-000-RS

1U flex ATX 150W Power Supply



## Features

1U flex ATX 150W Power Supply

## Specifications

Input	
Voltage	90~264 VAC Full Range
Frequency	47 Hz ~ 63 Hz
Input Current	3A (RMS)@115VAC, 1.5A (RMS)@230VAC
Inrush Current	80A max. for 115VAC, 160A max. for 230VAC
Output	
Voltage	+3.3V/10A,+5V/14A,+12V/10A,-12V/0.3A,+5Vsb/2.5A
Over Voltage Protection	+3.3V: 3.7V-4.8V
	+5V: 5.55V-7.0V
	+12V1 : 13.3V-16V
Short Circuit Protection	+3.3V, +5V, +12V, -12V shutdown and latch off
General	
Watt	150
Efficiency	87%
MTBF	100000
Operating temperature	0°C ~ 50°C
Storage temperature	-20°C ~ 80°C
Dimensions	150 x 81.5 x 40.5
Output Connector	1 x 20+4-PIN ATX,
	1 x 4-pin 12V CPU,
	1 x HDD/CDROM,
	1 x FDD,
	2 x SATA

## Ordering Information

63030-010150-000-RS	FLEX;FSP;FSP-150-50FBB;9PA1507909;Active PFC;Vin:90~264VAC;150W;150*81.5*40.5mm;;;80Plus(SILVER);Vout:ATX;ATX;CCL;RoHS
---------------------	---------------------------------------------------------------------------------------------------------------------------