

ACE-A160A

600 W PS/2 ATX Power Supply with ErP



Features

600 W PS/2 ATX Power Supply with ErP

Specifications

General	
Dimensions	140 x 150 x 86
Efficiency	85%
MTBF	100,000
Operating temperature	-5°C ~ 50°C
Output Connector	1 x 20+4-pin ATX, 1 x 4-pin 12V CPU, 9 x HDD/CDROM, 2 x FDD, 2 x SATA, 1 x Extra +5V(P10)
Storage temperature	-40°C ~ 80°C
Watt	600W
Input	
Voltage	90~265 VAC Full Range
Frequency	47 Hz ~ 63 Hz
Input Current	10A (RMS)@115VAC, 5A (RMS)@230VAC
Inrush Current	40A max. for 115VAC 80A max. for 230VAC
Output	
Voltage	+3.3V/25A,+5V/25A,+12V1/16A,+12V2/16A,+12V3/16A,+12V4/16A,-12V/0.5A,+5Vsb/4A
Over Voltage Protection	5V: 5.7V-6.5V 12V1 ~ 12V4: 13.3V-16.7V 3.3V: 3.9V-4.5V
Short Circuit Protection	+3.3V, +5V, +12V1, +12V2, +12V3, +12V4, 24V or -12V shutdown and latch off

Ordering Information

ACE-A160A-R11	600W PS/2 ATX Power Supply with ERP;CCL;RoHS
---------------	--