

63050-010500-010-RS

500 W ATX Mini Redundant Power Supply



Features

500 W ATX Mini Redundant Power Supply

Specifications

Environment	
Operating Temperature	0°C ~ 50°C
Storage Temperature	-20°C ~80°C
Input	
Voltage	90-264 VAC
Frequency	47-63 Hz
Input Current	6 A (RMS) @115 VAC, 3 A (RMS) @230 VAC
Inrush Current	40 A max. for 115 VAC, 80 A max. for 230 VAC
Output	
Voltage	+3.3V/20A,+5V/20A,+12V/40A,-5V/0.3A,-12V/0.5A,+5Vsb/3A
General	
Watt	500W
Efficiency	0.84
MTBF	100,000 hours
Dimensions	150 × 84× 190 mm

Ordering Information

63050-010500-010-RS	Redundant Power;FSP;FSP500-60MRB(S);9PR5000712;Active PFC;Vin:90~264VAC;500W;Vout:ATX;ATX;CCL;RoHS
63050-010500-000-RS	Redundant Power;FSP;FSP500-40MRB(M);9PA500C614;Active PFC;Vin:90~264VAC;500W;UNIT,meet 80plus(GOLD);Vout:12VDC/-12VDC/5VSB;Gold Finger;CCL;RoHS