

# iUCOM-4R

USB Module supports four RS-232/422/485 Port (RJ-45), RoHs



## Features

- » Quad-port RS-232/422/485
- » 1024 bytes transmit / 512 bytes receive FIFO
- » High-speed 16C550/16C650/16C750/16C850 compatible UARTs
- » Baud rate supports 115.2K, max. up to 6M

## Specifications

Form Factor	
Form Factor	USB2.0 (1*4pin, P=2.0)
	* USB Bridge to Quad Serial Port: WCH CH344
	* Buffer/Transceiver Series: Fintek 81435
Physical Characteristics	
Dimensions (LxWxH) (mm)	95mm * 40mm
I/O Interface	
I/O Interface	4 x External RS-232/422/485 : RJ-45
Environment	
Operating Temperature	0°C – 60°C
Storage Temperature	-30°C – 70°C
Humidity	5% ~ 95%, non-condensing
Certifications	
Safety & EMC	CE/FCC compliant

## Ordering Information

iUCOM-4R-R10	USB Module supports Quad RS-232/422/485 Port(RJ45), RoHs
--------------	--

## Packing List

1 x iUCOM-4R peripheral board	1 x QIG
1 x USB Cable(P=2.0)	1 x USB Cable(P=2.54)