

AUPS-B20

Output 100W UPS



Features

- » 100W (8.3A @ 12V) output
- » 56Wh, for more than 140 minutes operation time (depending on panel PC power requirements)
- » Rugged metal enclosure for standard VESA 75/100 mounting
- » Web-based, remote network management, no software installation required
- » Local PC-based monitoring software for input detection and battery status monitoring
- » Auto shut down when battery low
- » Remote DC output on/off switch for external switch installation
- » Provides stable power to the PC during line sags and spikes and absorbs power surges and transients, protecting expensive equipment

Specifications

| | |
|-------------------------|--|
| Capability (Watt) | |
| Capability (Watt) | 7.26V 5200 mA / 37.7W |
| Color | |
| Color | Black |
| General | |
| Dimensions | 152mm x 96mm x 28mm |
| Operating temperature | 0°C~40°C |
| Storage temperature | -20°C~50°C |
| Watt | 100W |
| Material | |
| Material | SECC |
| Weight | |
| Weight | 244g |
| Input | |
| Voltage | DC 9~36 V |
| Input Current | 1. Adapter is 12V-9A (Load is 100W) 2. Battery is 12V-9A (Load is 100W) |
| Output | |
| Voltage | DC +12V +/-5% |
| Over Voltage Protection | 1. Battery low is 10% of battery capacity 2. Shutdown 5% of battery capacity (Default) 3. The end of battery discharge voltage is 6V |

Ordering Information

| | |
|--------------|---|
| AUPS-B20-R20 | VESA 100, DC 9~36V input 100W UPS module with 14.52V;5200mAh, 4S2P Li-Ion battery,R20 |
|--------------|---|

Packing List

| | |
|--|---|
| 1 x DC power cable, 150mm, DC plug / 5.5 x 2.1 to DC plug / 5.0 x 2.5 without lock | 1 x USB cable, 200mm, USB type A male to mini USB |
| 1 x Remote switch cable, 1200mm | 1 x Screw kit |