

Alimentation > Alimentation de type PS/2

# 63010-010300-020-RS

300 W PS/2 ATX Power Supply with ErP



## Features

300 W PS/2 ATX Power Supply with ErP

## Specifications

| Input                    |   |
|--------------------------|---|
| Voltage                  | 90~264 VAC Full Range   |
| Frequency                | 47 Hz ~ 63 Hz   |
| Input Current            | 4A (RMS)@115VAC, 2A (RMS)@230VAC                                  |
| Inrush Current           | 80A max. for 115VAC, 160A max. for 230VAC                         |
| Output                   |   |
| Voltage                  | +3.3V/19A,+5V/16A,+12V1/17A,+12V2/17A,-12V/0.5A,+5Vsb/3A,-5V/0.1A |
| Over Voltage Protection  | +3.3V: 3.7V-4.3V  |
|                          | +5V: 5.74V-7.0V   |
|                          | +12V1 and +12V2: 13.4V-15.6V                                      |
| Short Circuit Protection | +3.3V, +5V, +12V or -12V shutdown and latch off                   |
| General                  |   |
| Watt                     | 300   |
| Efficiency               | 87%   |
| MTBF                     | 100000  |
| Operating temperature    | 0°C ~ 50°C  |
| Storage temperature      | -20°C ~ 80°C  |
| Dimensions               | 140 x 150 x 86  |
| Output Connector         | 1 x 20+4-PIN ATX,   |
|                          | 2 x 4-pin 12V CPU,  |
|                          | 7 x HDD/CDROM,  |
|                          | 1 x Graphics card power,  |
|                          | 1 x FDD,  |
|                          | 2 x SATA  |

## Ordering Information

|                     |  |
|---------------------|--|
| 63010-010300-020-RS | PS/2 Power;FSP;FSP300-70AGGBM;9PA300FJ08;Active PFC;Vin:90~264VAC;300W;meet 80plus(GOLD);Vout:ATX;ATX;CCL;RoHS |
|---------------------|--|