

DM-F65A

6.5"~15" DM-F IP65 Industrial Monitor



Features

- » Robust IP65 aluminum front bezel
- » Aesthetic ultra-thin bezel for seamless panel mount installation
- » DC input
- » DVI / VGA flexible video input solution
- » Resistive single touch
- » Wide temperature support

Specifications

| Display | |
|--------------------------|---|
| Backlight MTBF(hrs) | 50000 |
| Brightness(cd/m2) | 800 |
| Contrast Ratio | 600:1 |
| LCD Size | 6.5"(4:3) |
| Max Resolution | 640 (W) x 480 (H) |
| Environment | |
| Humidity | 10% to 95% (non-condensing) |
| IP Level | IP 65 compliant front panel |
| Operating Temperature | -20°C ~ 60°C (with air flow) |
| Storage Temperature | -20°C ~ 70°C |
| I/O Interface | |
| I/O Ports and Switches | 1 x VGA (DB-15) |
| | 1 x DVI |
| | 1 x USB 2.0 (touch) |
| | 1 x RS-232 (reserved for resistive touch ATO) |
| | 1 x Lockable 12V DC jack |
| LCD | |
| LCD Color | 16.2M |
| Pixel Pitch (mm) | 0.207 x 0.207 |
| Viewing Angle (H-V) | 160° / 140° |
| Physical Characteristics | |
| Cutout Dimensions | 180 x 140 |
| Dimensions (LxWxH) (mm) | 191.8 x 154.36 x 42.88 |
| Power | |
| Power adapter | 12V DC |
| Touch | |
| Touch Controller | Penmount 6000 |
| Touch Screen | 5-wire resistive single touch window |

| | |
|--------|------------|
| Weight | |
| Weight | 1.1/2.6 Kg |

Ordering Information

| | |
|---------------|--|
| DM-F65A/R-R10 | 6.5" 800 cd/m ² High luminance VGA LCD monitor with VGA, Aluminum die casting front panel, Black color,W/ USB resistive touch screen, R10 |
|---------------|--|

Packing List

| | |
|-------------------|---------------|
| 1 x Touch Pen | 1 x USB Cable |
| 1 x VGA Cable | 1 x Adapter |
| 1 x AC power cord | |