

KINO-DCM236

Mini-ITX SBC supports 6th Intel® Xeon® Processor E3 v5 series, Core™ i3, Celeron® per Intel® CM236, DDR4 with ECC support, HDMI™ 2.0, dual Intel® GbE, SATA 6Gb/s, USB 3.0, PCIe Mini, M.2, HD Audio and RoHS



Features

- » Mini ITX form factor with 6th Intel® Xeon® Processor E3 v5 series, Core™ i3, Celeron® support DDR4-2133 memory with ECC support
- » HDMI™ 2.0
- » ECC support
- » Triple display with independent audio
- » PCIe x16, dual PCIe Mini and M.2 A key feature support for various function module
- » Rich High speed I/O interface for USB 3.0 and SATA 6Gb/s
- » Support IEI jumpless

Specifications

| System | |
|--------------------------|--|
| CPU | 6th generation Intel® processor Intel® Xeon® processor E3-1505M v5 (up to 3.7GHz, quad-core, 8M Cache, TDP=45W) Intel® Xeon® processor E3-1505L v5 (up to 2.0GHz, quad-core, 8M Cache, TDP=25W) Intel® Core™ i3-6102E processor (up to 1.90GHz, dual-core, 3M cache, TDP=25W) Intel® Celeron® processor G3902E (up to 1.60GHz, dual-core, 2M cache, TDP=25W) |
| Chipset | Intel® CM236 |
| Memory | Two 260-pin 2133/1866 MHz dual-channel DDR4 ECC and non-ECC unbuffered SDRAM SO-DIMMs |
| Memory Max. | 64GB |
| Physical Characteristics | |
| Dimensions (LxWxH) (mm) | 170 X 170 |
| Net Weight | 450g |
| Storage | |
| Storage | 4 x SATA :6Gb/s(RAID 0/1/5/10 support) |
| I/O Interface | |
| Display Output | 3 x HDMI™ :2 X 1.4(up to 4096X2160@24Hz),1 X 2.0(up to 4096 X 2160@60Hz) 1 x LVDS 18/24-bit dual-channel (up to 1920x1200@60Hz) |
| Ethernet | 2 x LAN :LAN1: Intel® I219LM with (Intel® AMT 11.0 support) LAN2: Intel® I211 PCIe controller with NCSI support |
| Audio | Description: Realtek ALC662 HD Audio codec supports 5.1-channel 1 x Line out :on rear IO 1 x Mic :on rear IO 1 x Front Audio :2x5 pin |
| I/O Interface | 1 x External RS-232 3 x Internal RS-232 :1x9 pin, p=1.25 2 x Internal RS-232/422/485 :1x9 pin, p=1.25 4 x External USB 3.2 Gen1x1 4 x Internal USB 2.0 :2x4 pin, P=2.0 1 x PS/2 :1x6 pin |
| Expansion | 1 x PCIe x16 |

| | |
|-----------------------|---|
| | 2 x PCIe mini Card Slot :1 x Full-size slot(support mSATA), 1 X Half-size slot |
| | 1 x M.2(NGFF) :2230(A Key) |
| Power | |
| Power Consumption | 12V@6.93A (Intel Xeon E3-1505M V5 2.8GHz CPU with 32 GB (two 16 GB) 2133 MHz DDR4 memory) |
| Power Supply | 12V DC input |
| | 1 x External DC jack (4-pin DIN) |
| | 1 x Internal power connector (2x2 pin) |
| | Support AT/ATX mode |
| Environment | |
| Operating Temperature | -20°C ~ 60°C |
| Humidity | 5% ~ 95%, non-condensing |
| Certifications | |
| Safety & EMC | CE/FCC compliant |

Ordering Information

| | |
|---------------------|--|
| KINO-DCM236-E3E-R11 | Mini-ITX SBC supports 6th Intel® Xeon® E3-1505L v5(25W) Processor, DDR4 with ECC support, HDMI™ 2.0, SATA 6Gb/s, dual Intel® GbE, USB 3.2, PCIe Mini, M.2, HD Audio and RoHS |
| KINO-DCM236-E3-R11 | Mini-ITX SBC supports 6th Intel® Xeon® E3-1505M v5(45W) Processor, DDR4 with ECC support, HDMI™ 2.0, SATA 6Gb/s, dual Intel® GbE, USB 3.2, PCIe Mini, M.2, HD Audio and RoHS |

Packing List

| | |
|---|----------------|
| 1 x KINO-DCM236 single board computer with CPU cooler | 2 x SATA cable |
| 1 x I/O shielding | 1 x QIG |