


# 63010-010400-010-RS

400 W PS/2 ATX Power Supply with ErP



## Features

400 W PS/2 ATX Power Supply with ErP

## Specifications

Input	
Voltage	90~264 VAC Full Range
Frequency	47 Hz ~ 63 Hz
Input Current	5A (RMS)@115VAC, 2.5A (RMS)@230VAC
Inrush Current	80A max. for 115VAC, 160A max. for 230VAC
Output	
Voltage	+3.3V/21A, +5V/16A, +12V1/16A, +12V2/17A, -12V/0.5A, +5Vsb/3A, -5V/0.1A
Over Voltage Protection	+3.3V: 3.76V-4.3V +5V: 5.74V-7.0V +12V1 and +12V2: 13.4V-15.6V
Short Circuit Protection	+3.3V, +5V, +12V or -12V shutdown and latch off
General	
Watt	400
Efficiency	87%
MTBF	100000
Operating temperature	0°C ~ 50°C
Storage temperature	-20°C ~ 80°C
Dimensions	140 x 150 x 86
Output Connector	1 x 20+4-PIN ATX, 2 x 4-pin 12V CPU, 8 x HDD/CDROM, 1 x Graphics card power, 2 x FDD, 2 x SATA

## Ordering Information

63010-010400-010-RS	PS/2 Power;FSP;FSP400-70AGGBM;9PA400CH06;Active PFC;Vin:90~264VAC;400W;;;meet 80plus(GOLD),with ERP & on/off switch;Vout:ATX;ATX;CCL;RoHS
---------------------	---