

TANK-6000-C226

Support IPMI 2.0 via IEI iRIS solution, Intel® E3 1225 v3/i3 4330 high performance CPU



Features

- » Workstation with Intel® C226 chipset
- » Intel® E3 1225 v3/i3 4330 high performance CPU
- » Support two PCIe by 8 expansion cards
- » 4 x LAN port (two SFP fiber combo ports)
- » 3 x 2.5" HDD/SSD bay
- » Support IPMI 2.0 via IEI iRIS solution
- » Support programable OLED display module

Specifications

Color	
Color	Black
Dimensions	
Dimensions	310 x 199.5 x 112
Environment	
Humidity	5% ~ 95%, non-condensing
Operating Temperature	-20°C ~ 55°C with air flow (SSD)
Expansion Slots	
Expansion Slots	PCIe: 2 x PCIe x8 (Gen 3)
Form factor	
SBC Form Factor	CPU:
	Intel® Xeon® E3 1225-v3 3.2 GHz
	Intel® Core™ i3 4330 3.5 GHz
	Chipset: Intel® C226
	System Memory:
	4 x 240-pin DDR3 U-DIMM, 4 GB pre-installed (system max: 32 GB)
I/O Interface	
I/O Ports	4 x USB 3.0
	2 x USB 2.0
	Ethernet:
	4 x RJ-45
	1 x PCIe GbE by Intel® i217 PHY
	3 x PCIe by GbE Intel® i210
	Fiber:
	2 x Combo (SFP Fiber/RJ-45), combo with LAN 1/LAN 2
	COM Port: 2 x RS-232 (DB-9)
	Display: 1 x HDMI™, 1 x VGA
	Resolution:
	HDMI™: Up to 1920 x 1200@60Hz
	VGA: Up to 1920 x 1200@60Hz
	Audio: 1 x Line-out, 1 x Mic in
System	
Cooling method / System Fan	92 mm x 92 mm x 25 mm
Drive Bays	3 x 2.5' SATA 6Gb/s HDD/SSD drive bay
Weight	

Weight	2.5 kg/4.6 kg
--------	---------------

Ordering Information

TANK-6000-C226i-i3/4G-R11	Embedded System with Intel C226 chipset, Intel dual-core i3- 4330 3.5GHz ,TDP 54W,OLED indicator, 2 x PCIe by 8 expansion, 3 x 2.5" SATA HDD bay,DDR3 U-DIMM 4GB pre-installed (2 x 2GB), iRIS-2400 supported, 19/24V DC,RoHS
TANK-6000-C226i-E3/4G-R11	Embedded System with Intel C226 chipset, Intel quad-core Xeon E3-1225 v3 3.2GHz ,TDP 84W,OLED indicator, 2 x PCIe by 8 expansion, 3 x 2.5" SATA HDD bay,DDR3 U-DIMM 4GB pre-installed (2 x 2GB) , iRIS-2400 supported, 19/24V DC, RoHS

Packing List

1 x Power Adapter (With PSE & ErP Certified)	1 x Wall mount kit
1 x Screw pack	