



	POCm-W22C-ULT3	POCm-W24C-ULT3
LCD Size	22"	24"
Brightness(cd/m2)	250	250
Max Resolution	1920x1080	1920x1080
Contrast Ratio	1000:1	1000:1
Backlight MTBF(hrs)	30000	30000
Cooling method / System Fan	Fanless	Fanless
CPU	6th generation Intel® mobile ULT Core™ i7-6600U / Core™ i5-6300U / Celeron® 3855U	6th generation Intel® mobile ULT Core™ i7-6600U / Core™ i5-6300U / Celeron® 3855U
Storage	1 x 2.5" accessible SATA HDD bay 2 x M-key M.2 2242/60/80 (PCIe+SATA) with RAID	1 x 2.5" accessible SATA HDD bay 2 x M-key M.2 2242/60/80 (PCIe+SATA) with RAID
Bluetooth	V4.2 (M.2 2230 A-E key module)	V4.2 (M.2 2230 A-E key module)
Wi-Fi	IEEE 802.11 a/b/g/n/ac 2T2R module	IEEE 802.11 a/b/g/n/ac 2T2R module
Audio	2 x 3W Speaker	2 x 3W Speaker
Expansion	1 x Full-size/half-size PCIe Mini (PCIe+USB)	1 x Full-size/half-size PCIe Mini (PCIe+USB)
Power adapter	150W medical power adapter	150W medical power adapter
Operating Temperature	0°C~40°C	0°C~40°C
Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)
Storage Temperature	-20°C~60°C	-20°C~60°C
Color	White	White
Mounting	Wall, Stand and Arm VESA 100/75	Wall, Stand and Arm VESA 100/75
Dimensions (LxWxH) (mm)	543 x 350 x 71 mm	594.6 x 379.6 x 71 mm
Weight	7.07 kg without batteries 8.43 kg with 3 batteries	8.18 kg without batteries 9.53 kg with 3 batteries
Power Supply	3 slots for hot swappable battery pack	3 slots for hot swappable battery pack
Touch Screen	Projected capacitive type with 10-point multi-touch	Projected capacitive type with 10-point multi-touch
IP Level	Front: IP65, Back: IP32	Front: IP65, Back: IP32
Camera	5-megapixel CMOS front-facing camera with auto-focus and digital microphone	5-megapixel CMOS front-facing camera with auto-focus and digital microphone
System Cooling	Fanless	Fanless

Construction Front Panel	ABS+PC plastic with anti-bacterial material	ABS+PC plastic with anti-bacterial material
RAM	Two 260-pin 2400/2133MHz dual-channel DDR4 SO-DIMM, 4GB pre-installed (system max. 32GB)	Two 260-pin 2400/2133MHz dual-channel DDR4 SO-DIMM, 4GB pre-installed (system max. 32GB)
Microphone	digital microphone	digital microphone
I/O Ports and Switches	<ul style="list-style-type: none"> 2 x USB 2.0 (side) 4 x USB 3.0 port 2 x HDMI output 2 x GbE LAN port 2 x RS-232/422/485 1 x Audio out (side) + 1 x Mic in (side) 1 x Digital Mic 1 x DC jack 	<ul style="list-style-type: none"> 2 x USB 2.0 (side) 4 x USB 3.0 port 2 x HDMI output 2 x GbE LAN port 2 x RS-232/422/485 1 x Audio out (side) + 1 x Mic in (side) 1 x Digital Mic 1 x DC jack
OSD Function	<ul style="list-style-type: none"> 1 x Brightness up 1 x Brightness down 1 x Volume up 1 x Volume down 1 x Touch lock & LCD on/off 1 x Task Manager & Power on/off 	<ul style="list-style-type: none"> 1 x Brightness up 1 x Brightness down 1 x Volume up 1 x Volume down 1 x Touch lock & LCD on/off 1 x Task Manager & Power on/off
LED Function	<ul style="list-style-type: none"> 1 x RFID indicator 3 x Battery indicator (Color : Blue/Red) 1 x Power Indicator 	<ul style="list-style-type: none"> 1 x RFID indicator 3 x Battery indicator (Color : Blue/Red) 1 x Power Indicator
I/O Interface	<ul style="list-style-type: none"> 1 x AT/ATX Switch 1 x Mic 1 x Line out 2 x USB 2.0 4 x USB 3.2 Gen1x1 2 x LAN(GbE) 2 x RS-232 2 x HDMI 1 x Power In(19V DC jack) 2 x Speaker 	<ul style="list-style-type: none"> 1 x AT/ATX Switch 1 x Mic 1 x Line out 2 x USB 2.0 4 x USB 3.2 Gen1x1 2 x LAN(GbE) 2 x RS-232 2 x HDMI 1 x Power In(19V DC jack) 2 x Speaker