

TANK-600-D2550/N2600

Fanless Embedded System, Intel® Cedarview Dual Core Atom™ CPU



Features

- » Intel® Atom™ D2550 1.86 GHz dual-core processor / Intel® Atom™ N2600 1.6 GHz dual-core processor
- » Eight COM ports: six RS-232 and two RS-232/422/485
- » 6 x USB 2.0
- » Dual PCIe GbE LAN for high-speed network applications

Specifications

Color	
Color	Black C + Silver
Dimensions	
Dimensions	193.4 x 200 x 57
Environment	
Humidity	5% ~ 95%, non-condensing
Operating Temperature	-20°C ~70°C with air flow (SSD),
Expansion Slots	
Expansion Slots	1 x Full size (co-lay mSATA) 1 x Half size
Form factor	
SBC Form Factor	CPU: Intel® Atom™ D2550 1.86 GHz Intel® Atom™ N2600 1.6 GHz Chipset: Intel® NM10 System Memory: On-board DDR3 4/2 GB
I/O Interface	
I/O Ports	6 x USB 2.0 Ethernet: 2 x RJ-45 PCIe GbE by Realtek 8111E COM Port 6 x RS-232 (DB-9) 2 x RS-232/422/485 (DB-9) Display: 1 x VGA 1 x Line-out, 1 x Mic-in
System	
Cooling method / System Fan	Fanless
Drive Bays	1 x 2.5' SATA 3Gb/s HDD/SSD bay
Weight	
Weight	2.2 kg/3 kg

Ordering Information

TANK-600-CV-N2600-8C/2G-R11	Extend temperature Fanless embedded system with Intel® Cedarview N2600 1.6 GHz processor dual core CPU, with 2G DDR3 RAM onboard, 1xVGA, Dual GbE LAN, 6xUSB2.0 , 2xRS-232/422/485 , 6 x RS-232, RoHS
TANK-600-CV-D2550-8C/4G-R11	Extend temperature Fanless embedded system with Intel® Cedarview D2550 1.86GHz processor dual core CPU, with 4G DDR3 RAM onboard, 1xVGA, Dual GbE LAN , 6xUSB2.0 , 2xRS-232/422/485 , 6 x RS-232, RoHS

Packing List

1 x Power cord	1 x Power adapter (Meet PSE & ErP)
1 x Wall mount bracket	1 x Screw set