


iUCOM-4D

USB Module supports four RS-232/422/485 Port (DB-9), RoHs



Features

- » Quad-port RS-232/422/485
- » 1024 bytes transmit / 512 bytes receive FIFO
- » High-speed 16C550/16C650/16C750/16C850 compatible UARTs
- » Baud rate supports 115.2K, max. up to 6M

Specifications

| | |
|--------------------------|---|
| Form Factor | |
| Form Factor | USB2.0 (1*4pin, P=2.0) |
| | * USB Bridge to Quad Serial Port: WCH CH344 |
| | * Buffer/Transceiver Series: Fintek 81435 |
| Physical Characteristics | |
| Dimensions (LxWxH) (mm) | 140mm * 35mm |
| I/O Interface | |
| I/O Interface | 4 x External RS-232/422/485 : DB-9 |
| Environment | |
| Operating Temperature | 0°C – 60°C |
| Storage Temperature | -30°C – 70°C |
| Humidity | 5% ~ 95%, non-condensing |
| Certifications | |
| Safety & EMC | CE/FCC compliant |

Ordering Information

| | |
|--------------|---|
| iUCOM-4D-R10 | USB Module supports four RS-232/422/485 Port(DB9), RoHs |
|--------------|---|

Packing List

| | |
|-------------------------------|-----------------------|
| 1 x iUCOM-4D peripheral board | 1 x QIG |
| 1 x USB Cable(P=2.0) | 1 x USB Cable(P=2.54) |