

63010-010300-030-RS

300 W PS/2 ATX Power Supply with ErP

Features

300 W PS/2 ATX Power Supply with ErP



Specifications

Input	
Voltage	90~264 VAC Full Range
Frequency	47 Hz ~ 63 Hz
Input Current	4A (RMS)@115VAC, 2A (RMS)@230VAC
Inrush Current	80A max. for 115VAC, 160A max. for 230VAC
Output	
Voltage	+3.3V/19A,+5V/16A,+12V1/17A,+12V2/17A,-12V/0.5A,+5Vsb/3A,-5V/0.1A
Over Voltage Protection	+3.3V: 3.7V-4.3V +5V: 5.74V-7.0V +12V1 and +12V2: 13.4V-15.6V
Short Circuit Protection	+3.3V, +5V, +12V or -12V shutdown and latch off
General	
Watt	300
Efficiency	0.87
MTBF	100000
Operating temperature	0°C ~ 50°C
Storage temperature	-40°C ~ 70°C
Dimensions	140 x 150 x 86
Output Connector	1 x 20+4-PIN ATX, 2 x 4-pin 12V CPU, 7 x HDD/CDROM, 1 x Graphics card power, 1 x FDD, 2 x SATA

Ordering Information

--	--

switch;Vout:ATX;CCL;RoHS

63010-010300-030-RS

PS/2 Power;FSP;FSP300-70AGGBM;9PA300FJ07;Active
PFC;Vin:90~264VAC;300W;150*140*86mm;;;meet 80plus(GOLD),with ERP & on/off